Precise storage. For all varietals
The 5000 Cellaring Core Single-Zone can be set between 5–18°C for serving, or 12–14°C for cellaring all varietals for short or long-term.

Product Benefits & Features

Extendable Wooden Shelves. For easy access
Get to that one bottle you're looking for, easily, with Extendable Wooden Shelves on telescopic runners.

- Dynamic air technology
- Precision cooling system
- Reversible door

Preserve wine with Cellaring 3 Fundamentals
We help you treat your wine properly by providing storage that offers Cellaring 3 Fundamentals: temperature stability, a vibration free environment and a dark storage area.

Top LED Illumination. To see your collection properly
Premium lighting for your wines with Top LED Illumination. Your entire collection in the clear.

Product Specification

Series	5000	Noise Rating (dB)	D
Series	5000	Noise Rating (dB)	D
Series	5000	Noise Rating (dB)	D
Series	5000	Noise Rating (dB)	D
Energy Rating	G	Fridge Light Type	Internal. LED
Energy Rating	G	Fridge Light Type	Internal. LED
Energy Rating	G	Fridge Light Type	Internal. LED
Energy Rating	G	Fridge Light Type	Internal. LED
Fridge Capacity (L)	58	Main Colour	Black+Glass
Fridge Capacity (L)	58	Main Colour	Black+Glass
Fridge Capacity (L)	58	Main Colour	Black+Glass
Fridge Capacity (L)	58	Main Colour	Black+Glass
Fridge - Number of Shelves	6 Full Width	Built-in Dimensions (mm) (HxWxD)	822x300x550
Fridge - Number of Shelves	6 Full Width	Built-in Dimensions (mm) (HxWxD)	822x300x550
Fridge - Number of Shelves	6 Full Width	Built-in Dimensions (mm) (HxWxD)	822x300x550
Fridge - Number of Shelves	6 Full Width	Built-in Dimensions (mm) (HxWxD)	822x300x550
Dimensions (mm) (HxWxD)	820x295x571	Installation Type	BI Wide Door
Dimensions (mm) (HxWxD)	820x295x571	Installation Type	BI Wide Door
Dimensions (mm) (HxWxD)	820x295x571	Installation Type	BI Wide Door
Dimensions (mm) (HxWxD)	820x295x571	Installation Type	BI Wide Door
Minimum Ambient Temperature (°C)	16	Door Hinge Position	Right & Reversible
Minimum Ambient Temperature (°C)	16	Door Hinge Position	Right & Reversible
Minimum Ambient Temperature (°C)	16	Door Hinge Position	Right & Reversible
Minimum Ambient Temperature (°C)	16	Door Hinge Position	Right & Reversible

PSGBWC230DE00005